


# Safety Barrier Technical Conditions for Use

## T-LOK MASH F-TYPE Concrete Safety Barrier - Temporary

	<b>Issue Date:</b> 2 September 2022	<b>Proponent:</b> Saferoads Pty Ltd
	<p><b>These conditions take precedence over any instructions in the Product Manual.</b></p> <p>This document is a summary of the Austroads Safety Barrier Assessment Panel's assessment of the technical performance of the product against AS/NZS 3845 Parts 1 or 2 only. It does not consider procurement practices by individual Road Agencies.</p> <p>The Austroads Safety Assessment Panel may at any time, withdraw or modify this Technical Conditions for Use without notice.</p> <p>These acceptance conditions should be read in conjunction with the Product Manual and Austroads Guide to Road Design Part 6: Roadside Design, Safety and Barriers.</p> <p>Acceptance of this product does not place any obligation on the Northern Territory Government or its contractors, to purchase or use the product.</p>	

Status	<b>Accepted – may be used on the classified road network</b>
Product accepted	T-LOK MASH F-TYPE Concrete Safety Barrier  <u>Variants</u> 3.66m T-LOK MASH F-TYPE Concrete Safety Barrier - Temporary 5.40m T-LOK MASH F-TYPE Concrete Safety Barrier – Temporary Bespoke Wedge - to accommodate small radii  Variants that are NOT listed above are NOT recommended for acceptance.
Accepted Speed	100 km/h
Product Manual reviewed	Version 7.0 - November 2021
Product Manual	<a href="https://www.saferoads.com.au/t-lok-barrier">https://www.saferoads.com.au/t-lok-barrier</a>

### Design Requirements

Containment Level	Point of Redirection (m)		Tested Article Length (m)	Anchor/Post Spacing (m)	Dynamic Deflection (m)	Working Width (m)	Notes
	Leading	Trailing					
MASH TL3	21.9	36.6	58.5	Freestanding	1.27	1.88	

### Approved Connections

<i>Crash Cushions or Terminals must be fitted to both ends of a barrier</i>	
<b>Public Domain Products</b>	
W-Beam Guardrail	Not Permitted
Thrie-Beam Guardrail	Not Permitted
Concrete	Not Permitted

## T-LOK MASH F-TYPE Concrete Safety Barrier – Temporary

Proprietary Products	
UNIVERSAL TAU-M Crash Cushion	<ul style="list-style-type: none"> <li>• Refer Universal Tau-M Crash Cushion Technical Conditions for Use.</li> <li>• The T-Lok to Universal TAU-M Crash Cushion transition must be used to connect the crash cushion to the barrier.</li> <li>• Leading and trailing points of redirection are considered to be 0.</li> <li>• Reverse impacts into the transition section can produce a greater occupant severity value than preferred. Where reverse impacts are possible (e.g.: bi-directional traffic), a risk assessment must be completed and steps to mitigate the likelihood of reverse impact should be implemented.</li> </ul>
QUADGUARD M10 CZ Crash Cushion	<ul style="list-style-type: none"> <li>• Refer to QUADGUARD M10 CZ Crash Cushion Technical Conditions for Use.</li> <li>• The T-Lok MASH transition to end terminal must be used to connect the crash cushion to the barrier.</li> <li>• Leading and trailing points of redirection are considered to be 0.</li> <li>• Reverse impacts into the transition section can produce a greater occupant severity value than preferred. Where reverse impacts are possible (e.g. bi-directional traffic), a risk assessment must be completed and steps to mitigate the likelihood of reverse impact should be implemented.</li> </ul>
SLED Plastic Water Filled Crash Cushion	<ul style="list-style-type: none"> <li>•• <b>The installation is restricted to an impact speed limit of 80 km/h or less.</b></li> <li>•• <b>Refer to SLED Plastic Water Filled Crash Cushion Technical Conditions for Use.</b></li> <li>•• <b>The T-Lok to SLED Crash Cushion transition must be used to connect the crash cushion to the barrier.</b></li> <li>•• <b>This is a gating device.</b></li> </ul>
ABSORB-M Crash Cushion	<ul style="list-style-type: none"> <li>• <b>The installation is restricted to an impact speed of 80 km/h or less.</b></li> <li>• Refer to Absorb-M Crash Cushion Technical Conditions for Use.</li> <li>• The T-Lok to Absorb-M Crash Cushion transition must be used to connect the crash cushion to the barrier.</li> <li>• This is a gating device.</li> </ul>
<b>LEGACY:</b> QUADGUARD CZ Crash Cushion	<ul style="list-style-type: none"> <li>• <b>LEGACY status recommended from 1 January 2021.</b></li> <li>• Refer to QUADGUARD CZ Crash Cushion Technical Conditions for Use.</li> <li>• The T-Lok MASH Concrete Safety Barrier adjacent to the Quadguard CZ Crash Cushion must be anchored to the pavement as required by the Product Manual.</li> <li>• The T-Lok to Quadguard CZ Crash Cushion transition must be used to connect the crash cushion to the barrier.</li> <li>• Leading and trailing points of redirection are considered to by 0.</li> <li>• Reverse impacts into the transition section can produce a greater occupant severity value than preferred. Where reverse impacts are possible (e.g. bi-directional traffic), a risk assessment must be completed and steps to mitigate the likelihood of reverse impact should be implemented.</li> </ul>
<b>LEGACY:</b> ABSORB 350 Plastic Terminal	<ul style="list-style-type: none"> <li>• <b>LEGACY status recommended from 1 January 2021.</b></li> <li>• <b>The installation is restricted to an impact speed of 70 km/h or less.</b></li> <li>• Refer to ABSORB 350 Terminal Technical Conditions for Use.</li> <li>• The T-Lok MASH to AB350 Terminal must be used to connect the terminal to the barrier.</li> <li>• This is a gating terminal.</li> </ul>

## T-LOK MASH F-TYPE Concrete Safety Barrier – Temporary

### Design Guidance

Minimum installation length	58.5 metres between crash cushions/terminals (tested article)
System width (m)	0.61
Minimum distance to excavation (m)	1.27 – measured from the face of the barrier on the works side
Slope limit	5%
Systems conditions	Installation on top of a kerb is not recommended
Gore area use	Permitted
Pedestrian area use	Permitted
Cycleway use	Permitted
Frequent impact likely	Permitted
Remote location	Permitted
Median use	Permitted

Foundation Pavement Conditions					
Pavement	Use	Max Accepted Impact Speed (km/h)	Post/Pin Spacing (m)	Post/Pin Type	Pavement Construction
Concrete	Permitted	100 km/h			<u>Freestanding</u> Foundation pavement conditions must be smooth and free of snag points, kerbs or obstructions that may interfere with the operation of the product
Deep lift asphaltic concrete					
Asphaltic concrete over granular pavement					
Flush seal over granular pavement					
Unsealed compacted formation					

**Note: Installation in pavement conditions not permitted above have not been justified to the Panel's satisfaction.**