

GENERAL:

- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH CONTRACT DOCUMENTS AND WITH SUCH OTHER WRITTEN INSTRUCTIONS DURING THE COURSE OF THE CONTRACT. READ THE DRAWINGS CAREFULLY AND REFER ANY DISCREPANCIES TO THE SUPERINTENDENTS REPRESENTATIVE FOR DECISION PRIOR TO PROCEEDING WITH THE WORK.
- ALL DIMENSIONS RELEVANT TO SETTING OUT AND OFF-SITE WORK SHALL BE VERIFIED BY THE CONTRACTOR PRIOR TO ANY CONSTRUCTION AND FABRICATION. DO NOT OBTAIN DIMENSIONS BY SCALING FROM THE DRAWINGS.
- REFER TO CIVIL DRAWINGS FOR DETAILS OF THE SITE SPECIFIC REQUIREMENTS FOR EACH BUS SHELTER.
- ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE (U.N.O.). WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH THE RELEVANT STANDARDS ASSOCIATION OF AUSTRALIA (SAA) CODES AND RELEVANT BUILDING AUTHORITY.
- ALL CIRCULATION SPACES, SIGNAGE, SURFACE INDICATORS (TGSi), GRABRAILS, DIMENSIONS AND STANDARD LAYOUT FOR DISABILITY ACCESS AND MOBILITY SHALL COMPLY WITH THE CURRENT VERSION OF AS 1428.1-2009 AND DISABILITY DISCRIMINATION ACT.
- THE BUILDER SHALL BE RESPONSIBLE FOR THE STRUCTURE DURING INSTALLATION AND PROVIDE ADEQUATE PROPPING, SUPPORT AND SAFETY BARRIERS/FENCES AS REQUIRED ON SITE.
- WHERE DTC STANDARDS ARE REFERENCED THESE REFER TO STANDARDS WITHIN THE NORTHERN TERRITORY DEEMED TO COMPLY MANUAL PREPARED BY THE DEPARTMENT OF INFRASTRUCTURE, PLANNING & LOGISTICS.
- THE STRUCTURAL WORK SHOWN ON THESE DRAWINGS HAS BEEN DESIGNED FOR THE FOLLOWING LOADS (TO AS 1170.2-2011 AND AS 1170.1-2002):

WIND LOADS (IN ACCORDANCE WITH AS 1170.2-2011)	
IMPORTANCE LEVEL,	2
M _s , M _t	1 , 1
WIND REGION	C
REGIONAL WIND SPEEDS, V ₅₀₀ V ₂₀	69.3m/s (ULS) 45m/s (SLS)
TERRAIN CATEGORY	2
INTERNAL PRESSURE COEFFICIENT (C _{pi})	-
LIVE LOADS (IN ACCORDANCE WITH AS 1170.1-2002)	
FLOOR - SLAB	5kPa
THE ALLOWABLE FOUNDATION BEARING PRESSURE	100kPa
CONCRETE EXPOSURE CLASSIFICATION	B2 > 1KM FROM COAST LINE

DEEMED TO COMPLY (DTC) REFERENCES:

- THE FOLLOWING TABLE LISTS CLADDING PRODUCTS TO BE USED FOR THIS STRUCTURE & FIXING REQUIREMENTS IN ACCORDANCE WITH THE DTC MANUAL. EQUAL OR BETTER PRODUCTS OTHER THAN THOSE LISTED (AND COVERED BY THE DTC MANUAL) MAY SUBSTITUTE WITH WRITTEN APPROVAL FROM THE SUPERINTENDENT:

	ELEMENT
	ROOF CLADDING
MANUFACTURER	BLUESCOPE LYSAGHT
PRODUCT	CUSTOM ORB
DTC DRAWING No.	M/312/01

FOUNDATIONS:

- FOUNDATION MATERIAL (AFTER EXCAVATING) IS ASSUMED TO HAVE A SAFE BEARING CAPACITY OF 100kPa. CONTRACTOR TO VERIFY SOIL BEARING PRESSURE PRIOR TO CONSTRUCTION.
- SUB-BASE FOR SLAB ON GROUND AND BACKFILL OVER FOOTINGS SHALL BE APPROVED GRANULAR MATERIAL, COMPACTED IN LAYERS OF 150mm MAX. TO AT LEAST 95% MAXIMUM MODIFIED DRY DENSITY (MMDD) IN ACCORDANCE WITH AS 1289-2014
- SURFACE TO BE STRIPPED OF ALL ORGANIC MATTER (E.G. TOP SOIL). PROOF ROLL SUBGRADE TO 95% MMDD.
- TESTING OF MATERIALS AND FOR COMPACTION SHALL BE DETERMINED BY THE SUPERINTENDENT IF NECESSARY.
- FOUNDATIONS SHALL BE INSPECTED PRIOR TO PLACEMENT OF CONCRETE.

CONCRETE:

- ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH AS 3600-2009.
- ALL FORMWORK SHALL CONFORM TO AS 3610-1995. RE-SHORING IS NOT PERMITTED.
- CONCRETE CHARACTERISTICS SHALL BE AS FOLLOWS U.N.O.

STRUCTURAL ELEMENT	COMPRESSIVE STRENGTH (F'c-28 DAYS MPa)	SLUMP (mm)	MAX. AGGREGATE SIZE (mm)
MASS CONCRETE FOOTPATHS	25	65 ± 15	20
SHELTER SLAB ON GROUND	32	65 ± 15	×10 exp. agg.

* USE 50/50 QUANTITY KATHERINE AND MT BUNDY 10mm AGGREGATE, FOR EXPOSED FINISH ON THE SLAB

- THERE SHALL BE NO CHANGES OF LEVEL BETWEEN EXISTING FOOTPATH/KERB AND THE NEW CONCRETE SLAB.
- ENSURE TACTILE INDICATORS ARE SECURELY FIXED.
- DIMENSIONS OF CONCRETE ELEMENTS IN THESE DRAWINGS DO NOT INCLUDE APPLIED FINISHES THICKNESS.
- ALL FORMED EDGES AND CORNERS OF CONCRETE MEMBERS SHALL HAVE 20mm CHAMFERS U.N.O.
- NO ADMIXTURES ARE TO BE USED WITHOUT WRITTEN APPROVAL OF THE SUPERINTENDENT.
- ALL CONCRETE TO BE COMPACTED USING MECHANICAL VIBRATION.
- NO HOLES OR CHASES OTHER THEN THOSE SHOWN ON THESE DRAWINGS SHALL BE MADE IN CONCRETE WITHOUT PRIOR APPROVAL OF THE SUPERINTENDENT.
- THE CONCRETE SLAB IN AND ATTACHED TO THE SHELTERS SHALL BE CLEANED BY ACID WASHING AND COATED TO PROVIDE A IMPERVIOUS SURFACE WITH 2 COATS OF CLEAR SOLVENT SEALER AS PER MANUFACTURERS DIRECTIONS.

COLOUR SCHEDULE:

STRUCTURE COLUMNS - GRAPHITE GREY - AUSTRALIAN STANDARD COLOUR - N65
 STRUCTURE ROOF BEAMS - BLUE JADE - AUSTRALIAN STANDARD COLOUR - T24
 SEAT STRUCTURE - SILVER GREY - AUSTRALIAN STANDARD COLOUR - N24
 FRONT LEADING EDGE - GOLDEN YELLOW - AUSTRALIAN STANDARD COLOUR - Y14

SOLAR LIGHTING

OPERATING COMPONENTS FOR BUS SHELTER SOLAR LIGHTS

- 1 x 80W SOLAR MODULE
- 1 x PV x 690T AGM BATTERY
- 1 x MORNING STAR SL OL REGULATOR/TIMER
- TRI-LOBIAL SECURITY BOLTS
- UV POLYCARBONATE LENS

LIGHT TO COME ON AT 1800hrs TO 2400hrs & ON AGAIN 0500hrs TO 0700hrs

TACTILE NOTES:

PROVIDE TILE TACTILE GROUND SURFACE INDICATORS (TGSis) AND INSTALL IN ACCORDANCE WITH MANUFACTURER SPECIFICATION AND COMPLY WITH CURRENT AS 1428.1 REQUIREMENT. USE SURFACE APPLIED TILES ON EXISTING CONCRETE SURFACES AND CAST IN TILES ON NEW CONCRETE. CONFIRM CONTRAST COLOR WITH SUPERINTENDENT PRIOR TO INSTALLATION.

STEELWORK:

- ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH AS 4100-1998 AND AS 1554-2014, BUILDING CODE OF AUSTRALIA (BCA) AND NT WORK SAFE REGULATIONS.
- ALL WELDS TO BE 6mm CONTINUOUS SPECIAL CLASS FILLET WELDS U.N.O.
- ALL WELDS SHALL BE PREFORMED BY A QUALIFIED WELDER IN ACCORDANCE WITH AS 1554-2014 AND WITH E41XX ELECTRODES AND MAGNETIC PARTICLE TESTED.
- ALL BOLT TYPES (AND DESIGNATIONS WHERE USED) SHALL BE AS FOLLOWS:
 - 4.6/S - COMMERCIAL BOLTS TO AS 1111-2015 AND AS 1112-2015 SNUG TIGHT.
 - 4.8/S - HIGH STRENGTH STRUCTURAL BOLTS, NUTS AND HARDENED WASHERS TO AS 1252-1996, SNUG TIGHTLY ONLY.
- ALL BOLTS, NUTS AND WASHERS INCLUDING H.D. BOLTS/REO ARE TO BE TOP DIP GALVANISED. ALL CAST-IN FERRULES AND CHEMICAL ANCHORS TO BE PASSIVATED ZINC COATED. ALL GALVANISED COMPONENTS CAST-IN TO CONCRETE MUST BE PASSIVATED.
- ALL STEELWORK SHALL HAVE STEEL GRADE AS FOLLOWS:
- ALL STRUCTURAL STEELWORK SHALL BE DEGREASED, GRIT BLASTED TO CLASS 2.5 AND SHOP PRIMED WITH ONE COAT OF INORGANIC ZINC SILICATE 75 MICRONS THICK IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATION.
- FINISH COATS TO STEELWORK TO BE HIGH GLOSS 2 COATS ZINC RICH TWO PACK AND TO BE COMPATIBLE WITH THE PRIMER AND IN ACCORDANCE WITH COLOR SCHEDULE AND SPECIFICATIONS.

STEEL MEMBER	STEEL GRADE	CORRESPONDING STANDARD
HOT ROLLED PLATES	250	AS 3678-2016
HOT ROLLED STEEL SECTIONS	300	AS 3679-2016
RECTANGULAR & SQUARE HOLLOW SECTIONS	350	AS 1163-2016


COLOUR SCHEDULE

STRUCTURAL FRAME	COLOUR	AUSTRALIAN STANDARD COLOUR CODE	COMMENTS
STRUCTURAL FRAME	GRAPHITE GREY	N65	
METAL PANELS	BLUE JADE	T24	
PANEL FRAMES	SILVER GREY	N24	
FRONT LEADING EDGE OF CORNER COLUMN	GOLDEN YELLOW	Y14	REFER TYPICAL SIDE ELEVATION - CS-3701/CS-3706/CS-3710

DRAWING SCHEDULE


BUS SHELTER TYPE MODULE	DRAWING NUMBER	DRAWING SHEET TITLE
TYPE 14A - 3 BAY	CS-3700	GENERAL NOTES
	CS-3701	TYPICAL PLAN, ELEVATION & SECTION
	CS-3702	TYPICAL SECTIONS DETAILS
	CS-3703	SLAB LAYOUT PLAN AND DETAILS (OPTION 1)
	CS-3704	SLAB LAYOUT PLAN AND DETAIL (OPTION 2)
TYPE 14B - 4 BAY	CS-3705	ROOF FRAMING PLANS & DETAILS
	CS-3700	GENERAL NOTES
	CS-3706	TYPICAL PLAN, ELEVATION & SECTION
	CS-3702	TYPICAL SECTIONS DETAILS
	CS-3707	SLAB LAYOUT PLAN AND DETAILS (OPTION 1)
TYPE 14C - 4 BAY	CS-3708	SLAB LAYOUT PLAN AND DETAIL (OPTION 2)
	CS-3709	ROOF FRAMING PLANS & DETAILS
	CS-3700	GENERAL NOTES
	CS-3710	TYPICAL PLAN, ELEVATION & SECTION
	CS-3702	TYPICAL SECTIONS DETAILS
	CS-3711	SLAB LAYOUT PLAN AND DETAILS (OPTION 1)
	CS-3712	SLAB LAYOUT PLAN AND DETAIL (OPTION 2)
	CS-3709	ROOF FRAMING PLANS & DETAILS

DRAWING IS TYPICAL ONLY. OBTAIN BUILDING PERMIT BEFORE CONSTRUCTION.

<p align="center">WARNING</p> <p align="center">BEWARE OF UNDERGROUND SERVICES. THE LOCATIONS OF UNDERGROUND SERVICES ARE APPROXIMATE ONLY AND THEIR EXACT POSITION SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GIVEN THAT ALL EXISTING SERVICES ARE SHOWN.</p>					DRAWN CARDNO DATE 14.02.17	CHECKED CARDNO DATE 14.02.17		STANDARD DRAWINGS BUS SHELTERS & ASSOCIATED INFRASTRUCTURE						
					DESIGNED CARDNO DATE 14.02.17	CHECKED CARDNO DATE 14.02.17		SHELTER - TYPE 14A & TYPE 14B & TYPE 14C GENERAL NOTES						
2 REISSUED AS STANDARD DRAWING OCT 2018 N.V. EES/DIPL					DESIGN LEADER S.HATZI DATE 15/09/2017		DESIGN DIRECTOR S.JACKSON DATE 15/09/2017		FILE No. -	ASSET No. -	SHEET No. 1 OF 6	DRAWING No. CS-3700	AMEND. 2	SHEET SIZE A1
1 ADDITIONAL NOTES APR 2018 N.V. EES/DIPL														
0 ISSUED AS A STANDARD DRAWING SEPT 2017 J.LEESON EES/DIPL														
No. DESCRIPTION DATE NAME DEPT/COMPANY														
AMENDMENTS														

CONCURRED STRUCTURAL ONLY

NORTHERN TERRITORY GOVERNMENT
 DEPARTMENT OF INFRASTRUCTURE, PLANNING & LOGISTICS
 Level 4, Highway House, Palmerston Circuit, Palmerston
 PO Box 61, Palmerston NT 0831

Signed:  02/10/18
 Registration No.: 33896ES