


**TYPICAL CROSS SECTION**



**NOTES:**

1. TABLE DRAINS TO BE FREE DRAINING AND MINIMUM 400mm DEPTH BELOW NATURAL SURFACE.
2. MAINTAIN EXISTING LONGITUDINAL AND VERTICAL ALIGNMENT.
3. TABLE DRAIN BLOCK TO BE COMPACTED AS SPECIFIED.
4. WINDROWS TO BE CUT DOWN TO NATURAL SURFACE AND INCORPORATED INTO EXISTING FORMATION.
5. SHOULDER MATERIAL MAY BE WON FROM TABLE DRAINS AND TABLE DRAIN BATTER, UNLESS OTHERWISE DIRECTED.

DATES STAGES FILES

1	NOTES ALTERED	JAN 2010	K.S.	
No.	DESCRIPTION	DATE	NAME	DEPT/COMPANY
AMENDMENTS				

DRAWN	CHECKED
DATE	DATE
DESIGNED	CHECKED
DATE	DATE
DESIGN PROJECT LEADER	PROJECT OFFICER
DATE	DATE



Department of Construction & Infrastructure

**STANDARD SPECIFICATION FOR ROAD MAINTENANCE WORKS**  
**9m GRAVEL PAVEMENT - TYPICAL CROSS SECTION**

FILE No.	ASSET No.	SHEET No.	DRAWING No.	AMEND.	SHEET SIZE
		OF	<b>CS2104 - 1</b>		<b>A4</b>