



**GENERAL NOTES:**

1. TACTILE INDICATORS TO CONFORM TO AS 1428.4
2. ALL CONCRETE TO BE N20
3. CONCRETE PAVING TO BE FINISHED WITH A STEEL TROWEL FOLLOWED BY LIGHT BRUSHING WITH A MOIST HAIR BROOM.
4. CONCRETE JOINTING :
  - i) CONSTRUCTION JOINTS - ROUGHEN AND CLEAN FACE OF HARDENED CONCRETE BEFORE PLACING FRESH CONCRETE AGAINST IT. REMOVE SOFT MATERIAL, FOREIGN MATTER AND LAITANCE.
  - ii) EXPANSION JOINTS - PROVIDE EXPANSION JOINTS AT 6m MAX. CTRS. AND AT JUNCTIONS WITH OTHER CONCRETE STRUCTURES. JOINTS TO BE 10mm WIDE OVER FULL LENGTH AND FILLED WITH A BITUMEN IMPREGNATED FIBROUS FILLER.
  - iii) DUMMY JOINTS - PROVIDE TRANSVERSE VERTICAL GROOVES 20mm MIN. DEPTH AT RIGHT ANGLES TO THE OUTER EDGE OF THE CONCRETE WORKS. JOINTS TO BE PLACED AT 2.0m MAX. CENTRES.
5. BUS STOP POST:
 

GENERAL BUS STOP POST TO BE PAINTED GOLDEN YELLOW 28659225  
SCHOOL BUS STOP POST TO BE PAINTED BLUE REFLEX
6. BUS STOP STICKER :
  - i) APPLY STICKERS ON TWO OPPOSITE SIDES OF POST.
  - ii) GENERAL BUS STOP STICKER TO BE BLACK ON YELLOW REFLECTIVE (3M 3271 YELLOW OR EQUIVELANT )
  - iii) SCHOOL BUS STOP STICKER TO BE WHITE ON CL2 BLUE REFLECTIVE (3M 3290 WHITE OR EQUIVELANT )

**NOTES :**

\* ENSURE THERE IS A WHEELCHAIR CROSSING WITHIN APPROX. 30m OF THE BUS STOP. IF THERE IS NO WHEELCHAIR CROSSING, INSTALL A STD WHEELCHAIR CROSSING AT A LOCATION TO BE NOMINATED BY THE SUPERINTENDENT. REFER TO C(S) 1202 FOR WHEELCHAIR CROSSING DETAILS.

- (A) FONT : HIGHWAY "E" 15 HIGH x 8 WIDE @ 45 DEGREES.
- (B) 70 x 805 mm BUS STOP STICKER REFER TO NOTES 5 & 6 FOR DETAILS.
- (C) FONT : HIGHWAY "E" 65 HIGH x 50 WIDE, WITH LETTER SPACING OF 25mm.

**BUS STOP STICKER DETAIL**  
NTS

DRAFT

DRAWN	K.S.	CHECKED	
DATE	MAY 2007	DATE	MAY 2007
DESIGNED		CHECKED	
DATE		DATE	
DESIGN PROJECT LEADER		PROJECT OFFICER	
DATE		DATE	MAY 2007



STANDARD DRAWING  
BUS STOP WITH TACTILE INDICATORS

FILE No.	ASSET No.	SHEET No.	DRAWING No.	AMEND.	SHEET SIZE
		1 OF 1	C(S)1823-0		A1

SDATES \$TIMES \$FILES

No.	DESCRIPTION	DATE	INIT.
	AMENDMENTS		