


TYPICAL CROSS SECTION



NOTES:

1. TABLE DRAINS TO BE FREE DRAINING AND MINIMUM 400mm DEPTH BELOW BASE OF GRAVEL PAVEMENT.
2. MAINTAIN EXISTING LONGITUDINAL AND VERTICAL ALIGNMENT.
3. TABLE DRAIN BLOCK TO BE COMPACTED AS SPECIFIED.
4. WINDROWS TO BE CUT DOWN TO NATURAL SURFACE AND INCORPORATED INTO EXISTING FORMATION.
5. SHOULDER MATERIAL MAY BE WON FROM TABLE DRAINS AND TABLE DRAIN BATTER, UNLESS OTHERWISE DIRECTED.

DATES SIZES

3	DRAWINGS CS2100-2 & SC3101-1 AMALGAMATED	JAN 2010	K.S.	
2	PAVEMENT WIDTH ADDED TO TITLE & NEW LOGO ADDED.	JULY 06	K.S.	
1	COMPACTION REQUIREMENTS REVIEWED.	NOV.02	WHAM	
No.	DESCRIPTION	DATE	NAME	DEPT./COMPANY
AMENDMENTS				

THIS DRAWING WAS CREATED FROM REDUNDANT CS2007-1 & CS2101-1.

DRAWN	CHECKED
DATE DESIGNED	DATE CHECKED
DATE DESIGN PROJECT LEADER	DATE PROJECT OFFICER
DATE	DATE



STANDARD SPECIFICATION FOR 8.0m GRAVEL PAVEMENT RESURFACING TYPICAL CROSS SECTION			
FILE No.	ASSET No.	SHEET No.	DRAWING No.
		OF	CS2100 - 3
			AMEND. SHEET SIZE
			A4